



Plant & Transport Solutions

Explore Industrial Park | Explore Way | Stetley | Worksop S80 3PD
 W: exploretransport.co.uk | W: exploreplantire.co.uk | T: 01322 733 060

Company Registration N°: 09403776 | VAT: 220586132

HIAB X-HIPRO 658 BASIC DATA

Technical data	HIAB XS 658 EP-6
Max. lifting capacity (kNm)	544
Outreach, hydraulic extensions (m)	17
Outreach - Lifting capacity, hydraulic extension First boom 10 deg, Second boom horizontal	5.1 / 10900
	6.7 / 8000
	8.6 / 6000
	10.6 / 4750
	12.7 / 3850
	14.7 / 3250
	16.9 / 2820
Slewing angle (°)	endless
Height in folded position (mm)	2600
Width in folded position (mm)	2550
Installation space needed (mm)	1507
Installation space needed (including rotation space) (mm)	1595
Weight, "standard" crane, without stabilisers (kg)	5545
Weight, frame attachments (kg)	78-123
Weight, stabiliser equipment, 9 m span (kg)	1015-1123

This table shows a few examples of models, and represents some of all options available. With the opportunity to configure your crane, we can provide you with a crane perfectly tailored to your needs.

Please contact your local dealer for more information on the variety of options we can offer.