

| | | | | |
|---|--|--|---------------------------|-----------------------------|
| Payload (kg) | Single Cab | 1,030 | - | - |
| | Extra Cab | 1,000 | - | - |
| | Double Cab | 1,030 Active 1,025 Icon, Invincible | | 1,015 1,010 |
| TOWING CAPACITY | | | | |
| Braked (kg) | | 3,500 | 3,500 | 3,500 3,500 |
| Unbraked | | 750 | 750 | 750 750 |
| EXTERIOR DIMENSIONS | | S/CAB | E/CAB | D/CAB |
| Overall length (mm) | | 5,325 | 5,325 | 5,325 |
| Overall width (mm) | | 1,800 | 1,855 | 1,855 1,900 Invincible X |
| Overall height (mm) | | 1,795 | 1,810 | 1,815 |
| Wheelbase (mm) | | 3,085 | 3,085 | 3,085 |
| Front track (mm) | | 1,500 | 1,540 | 1,540 |
| Rear track (mm) | | 1,510 | 1,550 | 1,550 |
| Front overhang (mm) | | 990 | 985 | 985 |
| Rear overhang (mm) | | 1,255 | 1,255 | 1,255 |
| Min. running ground clearance (mm) | | 277 | 289 | 310 |
| Angle of approach (deg) | | 29 | 29 | 29 |
| Angle of departure (deg) | | 25 | 26 | 26 |
| Wading depth (mm) | | 700 | | |
| Drag coefficient (Cd, dependant on vehicle specification) | | 0.394 | 0.394 | 0.394 |
| INTERIOR DIMENSIONS | | S/CAB | E/CAB | D/CAB |
| Interior length (mm) | | 1,697 | 1,404 | 1,697 |
| Interior width (mm) | | 1,480 | 1,481 | 1,480 (front) 1,410 (rear) |
| Interior height (mm) | | 1,170 | 1,168 | 1,170 |
| Couple distance (mm) | | n/a | n/a | 841 |
| Headroom (mm) | | 997 | 997 (front) 969 (rear) | 997 (front) 969 (rear) |
| DECK DIMENSIONS | | S/CAB | E/CAB | D/CAB |
| Length (mm) | | 2,315 | 1,808 | 1,525 |
| Max. width (mm) | | 1,575 | 1,540 | 1,540 |
| Height (mm) | | 480 | 480 | 480 |
| WHEELS & TYRES | | | | |
| Wheels | 17in steel, 17 or 18in alloy | | | |
| Tyres | 265/65R17 – Active & Icon 265/60R18 – Invincible & Invincible X | | | |

ENDS

Ref:210129M